

## Silkolene®

### SILKOLENE SCOOT 2

MC-Syn Technology 2-Stroke engine oil for scooters and mopeds

#### Description

FUCHS SILKOLENE SCOOT 2 provides excellent anti-wear properties and is specifically designed for scooters, mopeds and minibikes. A clean burning formulation which combats pre-ignition, ring-sticking and spark plug fouling.

SILKOLENE SCOOT 2 contains a low ash additive system and exclusive anti-wear synthetic chemistry to ensure long engine life with freedom from plug fouling and heavy combustion chamber deposits.

#### Application

SILKOLENE SCOOT 2 is compatible with all types of fuel. It is designed for small capacity engines and is suitable for use with autolube injector systems or as a premix.

SILKOLENE SCOOT 2 is recommended for use between 33 and 50 to 1 (3% to 2%) but users are advised to always follow engine manufacturers' recommendations.

#### Advantages

- Promotes combustion chamber cleanliness
- Prevents spark plug fouling and pre-ignition through carbon build-up
- Resists ring sticking and piston seizure
- Low smoke formula

#### Specifications

- I ISO L-EGC
- JASO FC

# Product Information



## Further Information

### Typical Data: SILKOLENE SCOOT 2

Characteristics	Test Method	Unit	Result
SAE Rating			20W/30
Appearance	Visual		Red
Specific Gravity at 15°C	IP160		0.872
Kinematic Viscosity @ 100°C	IP71	mm <sup>2</sup> /s	9.5
Flash Point (Closed Cup)	IP34	°C	95
JASO/Suzuki Visible Smoke Rating(JASO M342)			93*

\* MINIMUM REQUIREMENT FOR JASO FC IS 85

Reviewed 21/04/2020 AB

FUCHS LUBRICANTS (UK) plc  
New Century Street, Hanley  
Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44 (0)1782 203700  
contact-uk@fuchs.com



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.